



- Motores de alta Eficiencia IE2
- Carcasa de Aluminio
- Grado de Protección : IP55
- Aislamiento clase F



**MOTORES 1500 rpm**

Código STR	r/min.	Número Polos	Eficiencia	Motor KW	IEC Tamaño Motor	Tipo	PVP Forma B-5 (Brida)	PVP Forma B-3 (Patas)
MTVTA0016	1500	4P	IE2	0,25	71A	M2AA	198	166
MTVTA0017				0,37	71B		220	187
MTVTA0001				0,55	80A		240	205
MTVTA0002				0,75	80D		271	240
MTVTA0010				1,10	90LB		311	275
MTVTA0003				1,50	90LD		372	323
MTVTA0004				2,20	100LC		440	395
MTVTA0005				3,00	100LD		527	473
MTVTA0006				4,00	112MB		613	559
MTVTA0007				5,50	132M		784	718
MTVTA0008				7,50	132MA		989	906
MTVTA0011				11,00	160MLA		1.470	1.356
MTVTA0015				15,00	160MLB		1.872	1.760



Forma B-3 (Patas)

**MOTORES 1000 rpm**

Código STR	r/min.	Número Polos	Eficiencia	Motor KW	IEC Tamaño Motor	Tipo	PVP Forma B-5 (Brida)	PVP Forma B-3 (Patas)
MTVTA0020	1000	6P	IE2	0,25	71B	M2AA	233	200
MTVTA0021				0,37	80A		253	220
MTVTA0022				0,55	80B		286	253
MTVTA0023				0,75	90LB		332	301
MTVTA0024				1,10	90LD		397	373
MTVTA0025				1,50	100LC		460	426
MTVTA0026				2,20	112MB		570	536
MTVTA0027				3,00	132S		715	666
MTVTA0028				4,00	132MB		871	830
MTVTA0029				5,50	132MC		1.057	1.027
MTVTA0030				7,50	160MLA		1.555	1.442
MTVTA0031				11,00	160MLB		2.072	1.964
MTVTA0032				15,00	180MLA		2.610	2.460



Forma B-5 (Bridas)

APLICACIONES  
 Industria en General  
 Turbinas centrifugas  
 Radiales Plug Fans  
 Bombas

